

Qty	Luminaire Image	Colour Temperature (K)	Luminaire	Light Source	Efficacy (lm/w)	Upward Light (ULOR)	CRI	Luminaire Lumens	Dimensions (mm) (L x W x H)	Specification Text
B		2700	Viva City PRO	(vcp) - 60w LED FW70	134	0.0%	>70	8059	525 x 250 x 102 625 x 288 x 102 775 x 320 x 102	The luminaire shall be manufactured from high-pressure die-cast aluminium. It shall have an LED efficacy of up to 150.0 lm/W and will be capable of producing up to 24,660 luminaire lumens at 4000K with a CRI >70. It shall have an asymmetric forward throw optic and is rated at IP66 and IK08.
C		3000	Alfresco Urban	(alu) - 20w LED	0	40.2%	>70	0	340 x 340 x 105	The luminaire shall be manufactured from high-pressure die-cast aluminium. It shall have an LED efficacy of up to 107.0 lm/W and will be capable of producing up to 2,147 luminaire lumens at 4000K with a CRI >80. It shall have an asymmetric forward throw optic and is rated at IP65 and IK08.
F(SS)		2700	Viva City PRO	(vcp) - 40w LED FWB70	105	0.0%	>70	4210	525 x 250 x 102 625 x 288 x 102 775 x 320 x 102	The luminaire shall be manufactured from high-pressure die-cast aluminium. It shall have an LED efficacy of up to 150.0 lm/W and will be capable of producing up to 24,660 luminaire lumens at 4000K with a CRI >70. It shall have an asymmetric forward throw optic and is rated at IP66 and IK08.
GJ(SS)		2700	Viva City PRO	(vcp) - 40w LED AYB70	81	0.0%	>70	3241	525 x 250 x 102 625 x 288 x 102 775 x 320 x 102	The luminaire shall be manufactured from high-pressure die-cast aluminium. It shall have an LED efficacy of up to 150.0 lm/W and will be capable of producing up to 24,660 luminaire lumens at 4000K with a CRI >70. It shall have an asymmetric forward throw optic and is rated at IP66 and IK08.
G		2700	Viva City PRO	(vcp) - 40w LED AYB70	81	0.0%	>70	3241	525 x 250 x 102 625 x 288 x 102 775 x 320 x 102	The luminaire shall be manufactured from high-pressure die-cast aluminium. It shall have an LED efficacy of up to 150.0 lm/W and will be capable of producing up to 24,660 luminaire lumens at 4000K with a CRI >70. It shall have an asymmetric forward throw optic and is rated at IP66 and IK08.
H		2700	Viva City PRO	(vcp) - 40w LED AY70	135	0.0%	>70	5409	525 x 250 x 102 625 x 288 x 102 775 x 320 x 102	The luminaire shall be manufactured from high-pressure die-cast aluminium. It shall have an LED efficacy of up to 150.0 lm/W and will be capable of producing up to 24,660 luminaire lumens at 4000K with a CRI >70. It shall have an asymmetric forward throw optic and is rated at IP66 and IK08.
0		4000	Please Select	Please Select -	0	0.0%	--	0	0	Specification Text
0		4000	Please Select	Please Select -	0	0.0%	--	0	0	Specification Text