

KLOU180

radial

Arcluce Code


0871001A-830-16

Ex Code

S7097-16 CEI

Code EAN

8054378310607



Technical information

Light source: LED, 3000K, CRI>80

Luminaire efficacy: 76lm/W

Luminaire: 19W, 1450lm

LED life time: > 60000h - L80 - B20 (Ta 25°C)

High colour consistency: < 3 SDCM

Power supply: 220-240V 50/60Hz

Wiring: ON/OFF

Optics: radial

Color: Grey - 16

Weight: 9.5 kg

Size: A: Ø 184mm
B: 1000mm

CE

IP66

IK09



0,09m²



850°

Appliance

- Die-cast aluminium body (EN 47100).
- Extruded aluminium pole.
- Double layer polyester powder paint resistant to corrosion and salt spray fog.
- Silicone rubber gaskets.
- AISI 316 stainless steel external screws.
- Reflector made of anodized aluminium with non-iridescent specular finishing.
- UV rays stabilized, 850°C glow wire test resistant, V2 self-extinguishing clear polycarbonate screen.

Installation


- Bollard installation.
- Double grommet M20 for through wiring.
- Die-cast aluminium base (EN 47100) for ground anchoring for rawlplugs.
- Supplied with power cable.

Note

- DIFFERENT ACCESSORIES TO BE ORDERED SEPARATELY.

Norm

- It complies with standards EN 60598-1 and EN 60598-2-1.



KLOU180

radial

Arcluce Code

0871001A-830-16

Ex Code

S7097-16 CEI

Code EAN

8054378310607



Specifications

The bollard light for outdoor lighting with a catchy cylindrical design
Die-cast aluminium body (EN 47100). Extruded aluminium pole. Double layer polyester powder paint resistant to corrosion and salt spray fog. Silicone rubber gaskets. AISI 316 stainless steel external screws. Reflector made of anodized aluminium with non-iridescent specular finishing. UV rays stabilized, 850°C glow wire test resistant, V2 self-extinguishing clear polycarbonate screen.
It complies with standards EN 60598-1 and EN 60598-2-1.
LED sources available in color temperatures 3000K
High color consistency < 3 SDCM and LED life time > 60000h - L80 - B20 (Ta 25°C).
System effectiveness, minimum 76lm/W
Luminaire in insulation class II.
DRIVER INCLUDED.
Bollard installation. Double grommet M20 for through wiring. Die-cast aluminium base (EN 47100) for ground anchoring for rawplugs. Supplied with power cable.
Brand ARCLUCE mod. KLOU180