



TRAIN

OUTDOOR
WALL SURFACE

p. 545

484896

1.0 NARROW

LED 6W | 220-240VAC | 50-60Hz
COB 3-step | incl. PS
aluminium powder coated

0.24kg

⊕

IP65

±0.3°

Ⓢ

★ 46°x5°

narrow up or narrow down

CODE

719143D

LIGHT COLOUR

LUMEN | CRI

CODE

3000K

120 | >80

4

4848127/134

2.0 NARROW

2x LED 3W | 220-240VAC | 50-60Hz
COB 3-step | incl. PS
aluminium powder coated

0.35kg

⊕

IP65

±0.3°

Ⓢ

★ 46°x5°

narrow up | narrow down | 48 x 48 x 134

CODE

719243D

LIGHT COLOUR

LUMEN | CRI

CODE

3000K

2x75 | >80

4

narrow up | flood down | 48 x 48 x 127

CODE

719253D

LIGHT COLOUR

LUMEN | CRI

CODE

3000K

80/200 | >80

4

505085

1.0

LED 6W | 220-240VAC | 50-60Hz
COB 3-step | phase-cut dim
aluminium powder coated

0.24kg

⊕

IP65

±0.3°

Ⓢ

★ 38°

CODE

719868W

719868D

719868B

LIGHT COLOUR

LUMEN | CRI

CODE

3000K

420 | >90

5

5050120

2.0

2x LED 4W | 220-240VAC | 50-60Hz
COB 3-step | phase-cut dim
aluminium powder coated

0.35kg

⊕

IP65

±0.3°

Ⓢ

★ 38°

CODE

719968W

719968D

719968B

LIGHT COLOUR

LUMEN | CRI

CODE


3000K

2x255 | >90

5

Rev. 001/2021-07

WEVER & DUCRÉ 646 – 647



1.0 OPAL

LED 7W | 220-240VAC
PCB 3-step | phase-cut dim
aluminium | stainless steel
opal PMMA | polyamide
0.25m cable


0.15kg IP65 0.3m

76-84 70 2-25

	CODE
	733168W
	733168L
	733168D
	733168B

LIGHT COLOUR	LUMEN CRI	CODE
3000K	350 >90	5

INTRA
OUTDOOR
CEILING RECESSED



2.0 SPOT

LED 7W | 220-240VAC
PCB 3-step | phase-cut dim
aluminium | stainless steel
clear lens | polyamide
0.25m cable

0.15kg IP65 0.3m 38°

76-84 70 2-25

	CODE
	733158W
	733158L
	733158D
	733158B

LIGHT COLOUR	LUMEN CRI	CODE
3000K	490 >80	4




ORIS

WALL RECESSED



p. 623



0.7

LED 1/2W | 350/700mA | 3Vf
PCB 3-step | excl. power supply
aluminium powder coated

0.28kg IP20 0.3~0.3~0.3

47x182 40 12-40

3000K | >80 CRI | 90/150lm

	CODE
	327161W4
	327161B4

ALWAYS USE


power supply

	CODE
350mA 6W	90213202
500mA 6W	90214201
700mA 6W	90215203

more power supplies on page 723

OPTIONAL

	CODE
recessed housing	
incl. plasterkit	90012039
concrete	
housing	90012044



1.3

LED 2/4W | 350/700mA | 6Vf
PCB 3-step | excl. power supply
aluminium powder coated

0.34kg IP20 0.3~0.3~0.3

115x117 40 12-40

3000K | >80 CRI | 180/300lm

	CODE
	327261W4
	327261B4

ALWAYS USE


power supply

	CODE
350mA 6W	90213202
500mA 6W	90214201
700mA 6W	90215203

more power supplies on page 723

OPTIONAL

	CODE
recessed housing	
incl. plasterkit	90012041
concrete	
housing	90012040



2.0

LED 2/4W | 350/700mA | 6Vf
PCB 3-step | excl. power supply
aluminium powder coated

0.42kg IP20 0.3~0.3~0.3

115x185 40 12-40

3000K | >80 CRI | 180/300lm

	CODE
	327361W4
	327361B4

ALWAYS USE

power supply

	CODE
350mA 6W	90213202
500mA 6W	90214201
700mA 6W	90215203

more power supplies on page 723

OPTIONAL

	CODE
recessed housing	
incl. plasterkit	90012043
concrete	
housing	90012042