

TECHNICAL SPECIFICATIONS

NOISE CONTROL

The level of sound pressure with equivalent weighing is less than 70 dB.

ELECTRICITY SUPPLY

ELECTRICITY CONSUMPTION		
OPTIONS	KW.	AMPS 230V
HIGH PRESSURE PUMPS PER BAY	2.2	9.64
	3	13.2
	4	17.1
HOT WATER ELECTRICAL GENERATOR (2.5 L)	4	28
HOT WATER ELECTRICAL GENERATOR (40 L)	6	28
HEATER 60 W	0.06	0.27

CONSUMPTION

CONSUMPTION OF PRODUCT

CONSUMPTION OF PRODUCT		
PRODUCT	LITRES/HOUR	WORKING PRESSURE - DOSING PUMP BAR
SHAMPOO	2.1	2.5
WAX		

SALT CONSUMPTION

CONSUMPTION OF SALT														
HARDNESS °HF	15	20	25	30	35	40	45	50	55	60	65	70	75	80
TREATED WATER (M³) BETWEEN REGENERATIONS	5.6	4.2	3.4	2.8	2.4	2.1	1.9	1.7	1.5	1.4	1.29	1.2	1.1	1.1
CONSUMPTION OF SALT (KG/M³)	1.4	1.4	1.4	1.4	1.4	1.4	1.4	1.4	1.4	1.4	1.4	1.4	1.4	1.4
If daily volume of softened water is 0.5 m³														
Salt consumption per month (kgs)	3.5	4.7	6	7	8.4	8.4	10.5	10.5	10.5	14	14	14	14	14
If daily volume of softened water is 1 m³														
Salt consumption per month (kgs)	7	8.4	10.5	14	14	14	21	21	21	21	21	21	21	21
If daily volume of softened water is 1.5 m³														
Salt consumption per month (kgs)	10.5	14	14	21	21	21	21	21	21	42	42	42	42	42
If daily volume of softened water is 2 m³														
Salt consumption per month (kgs)	14	14	21	21	21	21	42	42	42	42	42	42	42	42