



Project:
Palmer Park Sports Centre - Reading

Document:
External Lighting Impact Statement

Client:
Pellikaan Construction Ltd / Greenwich Leisure Limited (GLL)

Author:
Nick Macina

TLP Project No:
C7402



Thornley & Lumb Partnership Ltd
Building Services Consultant Engineers

Century House
257 Cutler Heights Lane
Bradford
BD4 9JG
Tel: +44 (0) 1274 687 755
Mob: +44 (0) 7867 397 322

Email: nick.macina@thornleylumb.co.uk
Website: www.thornleylumb.co.uk

Document Control

Document	External Lighting Impact Statement
Project	Palmer Park Leisure Centre - Reading
Client	GLL / Pellikaan
Job Number	C7402

Revision	Issue 01
Document Date	25 th November 2020
Prepared By	Nick Macina
Checked By	Martin Thornley
Description of Revision	First Issue



Executive Summary

This external lighting impact assessment Statement produced by Thornley & Lumb Partnership to support and demonstrates how the proposed development will meet the requirements of the planning application made by Pellikaan Construction Ltd. This report confirms that the impact of the external lighting has been carefully assessed to ensure that the existing environment can coexist with the proposed new build.

With this in mind the external lighting installation for the development has been designed to ensure minimal impact on the immediate, neighbouring surroundings and beyond the boundary of the site.

The lighting scheme proposed for this site has been designed using Holophane Factor Street luminaire which has excellent light distribution and lighting control minimising nuisance glare, overspill lighting, haze reduction & zero upward light. All luminaires are supplied by Holophane Lighting Group, who are market leaders in street & urban lighting in the UK.

The proposed external lighting to the development will comprise of :-

- 12 x 6m columns with LED slim post top luminaires (Holophane - Factor Street Light). The lighting heads provided are designed to minimise glare, spill & skyglow, with
- 11 x 1m bollards Luminaire have been used to illuminate walkways. (Holophane – Denver Elite Bollards).
- 9 x LED wall mounted Luminaire have been used to illuminate walkways and escape exit routes around the building perimeter. (Holophane – Denver Elite Wall Light).
- LED Emergency Over Door Escape Bulkheads. (where required)

The external lighting, both column, bollard and building mounted, shall be controlled via a time clock & Photo Cell daylight sensor, to prevent operation during daylight hours. Daylight sensors override on a manually switched lighting circuit is acceptable, the existing external lighting currently operates from dusk till dawn.

The precautions that have been undertaken at all stages of the design to mitigate the effect of the lighting installation, and although it cannot be considered as having zero effect on the existing environment, due to the operational times and restrictions that have been imposed and the high degree of light control that is proposed, we feel that the installation will have minimal impact to the surrounding area.



Contents

Document Control	i
Executive Summary	ii
1.0 Introduction.....	1
2.0 Site Location.....	2
2.1 Existing Site	2
2.2 Proposed Scheme.....	3
3.0 Lighting Standards	4
4.0 The Lighting Strategy	5
4.1 Methodology.....	5
4.2 Design Standards.....	6
4.3 Mitigation.....	0
4.4 Summary Impact Table for Lighting Issues	1
5.0 Control Measures.....	2
6.0 Luminaire Selection.....	3
7.0 Glossary.....	4
7.1 Symmetric & Asymmetric Distribution	4
7.2 Glossary of Terms.....	4
8.0 Design Measures for Biodiversity.....	5
9.0 Conclusion.	6
Appendix A – Proposed External Lighting Layout	7
Appendix B – Proposed Light Fitting Technical Submittal	7



1.0 Introduction

The lighting installation for the development has been carefully designed to ensure minimal impact on its surroundings beyond the boundary of the site, so that the illuminated car park can be a good neighbour to all adjacent areas.

In relation to the design of the new external lighting installation, a number of criteria have been identified and addressed as follows:

- If external lighting is required and if so are there any alternatives
- How much light is required
- How the illuminated car park can fit into the surroundings and neighbourly considerations.
- How skyglow (the brightening of the night sky around the development), glare (brightness of the lights' source when viewed against the dark sky) and light trespass / spill (spilling of light beyond the site boundary) can all be minimized.
- safety of vehicular and pedestrian movement;
- security of property and goods.

Various documents have been consulted and provide guidance on external lighting design namely: -

The Institute of Lighting Professionals (ILP formally the ILE), GN01:2020 Guidance note on the reduction of obtrusive light:

The ILP Guidance note sets out the industry standard for numerically measuring, (both through lighting design calculations and on site), the light spill from lighting into windows, sky glow, source luminance and building façade brightness. The ILP guidance note provides illuminance, luminance and percentage figures which must be satisfied both pre and post curfew for various types of environmental zone classifications.

Institute of Lighting Professionals (ILP formally the ILE), BATS Conservation Trust Lighting Guidance (January 2008) The Bat Conservation Trust and the ILE produced a paper in 2009, "Bats and Lighting in the UK", discussing the appropriate lighting levels, types of lamps, colour temperatures etc. which are suitable for lighting areas adjacent to bat houses.

Furthermore publications in section 3 – Lighting standards



2.0 Site Location

2.1 Existing Site

Palmer Park Leisure Centre/ Stadium is situated in Reading, Berkshire, RG6 1LF.

Vehicle access to the site is via Wokingham Road (A329) to the south of the site, with additional footpath access also from Palmer Park Road (A4), St Bartholomew's Road and London Road.

(OS grid reference SU739730).




Image 1: Google Earth Extract - Existing site location.

The site is within the grounds of Palmer Park on the eastern outskirts of Reading town centre. The further open space of Palmer Park is situated to the north and east, and includes areas of recreational grassland with strips of woodland around the boundaries and an athletics track to the east. Residential properties are situated to the south and west. Reading Cemetery with open grassland and patches of woodland is situated just over 200 metres to the east, otherwise, the area is built up and surrounded by residential properties. To the south approximately 530 metres lies Reading University Whiteknights Campus consisting of parkland, mixed deciduous woodland and Whiteknights Lake. The River Thames is just over 1.15 kilometres away.

Although the setting is urbanised, the small pockets of woodland and open grassland directly surrounding the site, are likely to be of ecological value to a diversity of birds, mammals, reptiles, amphibians and invertebrates.



2.2 Proposed Scheme

The proposed New development extension is to comprise of construction of a new two storey leisure centre including 25m 6 lane swimming pool, with changing facilities and large open area fitness suite at first floor level. The new extension is to be constructed on the land adjacent the existing building. The proposed development is to include areas of hard landscaping including new green open cell parking spaces, new coach drop off point, new walkways in to the complex from Palmer Park Ave, areas of soft landscaping to include planters, seating areas & cycle racks.




Image 2: Proposed site location (SBA Architect Layout)

With regards to the external lighting design to the proposed site there are a number of specific areas which will need lighting for safety and to allow tasks to be completed such as entrance ways, emergency escapes & fire exits and the car park itself. Furthermore, there are areas where lighting may be illuminated to enhance the visitor experience (these will be kept to a minimum) such as cycle racks, seating areas and the existing listed monument.

It is noted from the Preliminary Ecological Assessment (R2298b), section 1.1.7 states that consideration should be employed to particularly avoid lighting the tree lined margins.



3.0 Lighting Standards

3.1 The following external lighting standards and guidance documents will form the basis for assessment of the minimum lighting design standard to be provided for the development:

British Standards:

BS 5489-1:2020 Code of Practice for the design of road lighting – Part 1: Lighting of roads and public amenity areas

BS EN 13201, 2:2015 Road lighting – Part 2: Performance requirements

CIBSE Lighting Guides:

CIBSE Lighting Guide LG1 - (2018) The Industrial Environment

CIBSE Lighting Guide LG6 - (2016) The Exterior Environment

CIE Publications:

CIE 136- (2000) – Guide to the Lighting of Urban Areas. (replaces CIE 92-1992)

CIE 126- (1997) – Guidelines for minimizing Skyglow

ILE/CIBSE:

Lighting the Environment - A guide to good urban lighting

Guidance Notes for the Reduction of Obtrusive Light GN01 (2020)



4.0 The Lighting Strategy

4.1 Methodology

This assessment has been undertaken in the context of existing environmental conditions and takes account of the fact that existing lighting is installed on the site at present.

The proposed areas on the site requiring lighting are as follows:

- Main Car Park - The times of use will be per the facilities opening hours, 7 days a week with the column mounted luminaires being illuminated from dusk till dawn. Outside these hours the natural daylight available will be exploited.
- Overspill Car Parks - The times of use will be per the facilities opening hours, 7 days a week with the column mounted luminaires being illuminated from dusk till dawn. Outside these hours the natural daylight available will be exploited.
- Building Perimeter Walkways - The times of use will be per the facilities opening hours, 7 days a week with the building mounted & final exit door bulkheads being illuminated from dusk till dawn. Outside these hours the natural daylight available will be exploited.
- Site Specific Considerations at Palmer Park – careful consideration has been employed in the selection and locations of the column's & luminaires to further reduce over illumination of the tree lined margins.

Within the car parking areas, the client (GLL) are focused on maintaining a safe and secure car park and all car parks will be floodlit generally to 10 lux (ave) to allow full operation of any onsite CCTV system and safe access and egress to cars and facilities for staff & customers.

TLP have carried out lux level calculations and skyglow plots using professional desktop software developed specifically for the application of external lighting.



4.2 Design Standards

The proposed external lighting installation will be designed in accordance with the environmental zone classification E3 that is set out within ILE guidance for reduction of light pollution. The table below is an extract from the ILE guidance note and sets out the environmental zone classifications for different environmental conditions. We have adopted the obtrusive light limitations for this external lighting installation as prescribed for an E3 classification. All lighting has been designed to be within these parameters.

TABLE 1 – OBTRUSIVE LIGHT LIMITATIONS FOR EXTERIOR LIGHTING INSTALLATIONS							
Environmental Zone	Sky Glow ULR [Max %]	Light into Windows E_v [Lux] (1)		Source Intensity I [kcd] (2)		Building Luminance Before curfew (3)	
		Before curfew	After curfew	Before curfew	After curfew	Average, L [cd/m ²]	Maximum L [cd/m ²]
E1	0	2	1*	0	0	0	0
E2	2.5	5	1	20	0.5	5	10
E3	5.0	10	2	30	1.0	10	60
E4	15.0	25	5	30	2.5	25	150

Notes:

Environmental Zone classification:

E1: Intrinsically dark areas - National Parks, Areas of Outstanding Natural Beauty, etc

E2: Low district brightness areas - Rural or small village locations

E3: Medium district brightness areas - Small town centres or urban locations

E4: High district brightness areas - Town/city centres with high levels of night-time activity

ULR = Upward Light Ratio of the Installation and is the maximum permitted percentage of luminaire flux for the total installation that goes directly into the sky.

E_v = Vertical Illuminance in Lux normal to glazing Light Intensity in Candelas

L = Luminance in Candelas/m²

(1) Light into Windows – These values are suggested maximums and need to take account of existing light trespass at the point of measurement.

* Acceptable from public road lighting installations ONLY.

(2) Source Intensity – This applies to each source in the potentially obtrusive direction, outside of the area being lit. The figures given are for general guidance only and for some large sports lighting applications with limited mounting heights, may be difficult to achieve. If the aforementioned recommendations are followed, then it should be possible to further lower these figures.

(3) Building Luminance – This should be limited to avoid over lighting and relate to the general district brightness. In this reference building luminance is applicable to buildings directly illuminated as a night- time feature as against the illumination of a building caused by spill light from adjacent floodlights or floodlights fixed to the building but used to light an adjacent area.



4.3 Mitigation

It is envisaged that the Leisure Centre car park will be open all year to paying Customers / Staff / Visitors. Lighting will be switched by means of a timeclock (08.30 – 22:00) to ensure that the lights are not operating at all hours and controlled by suitably mounted photocell to ensure non-operation when there is adequate daylight available.

The proposed external lighting to the development will comprise of :-

- 12 x 6m columns with LED slim post top luminaires (Holophane - Factor Street Light). The lighting heads provided are designed to minimise glare, spill & skyglow, with
- 11 x 1m bollards Luminaire have been used to illuminate walkways. (Holophane – Denver Elite Bollards).
- 9 x LED wall mounted Luminaire have been used to illuminate walkways and escape exit routes around the building perimeter. (Holophane – Denver Elite Wall Light).
- LED Emergency Over Door Escape Bulkheads. (where required)

The light fitting heads for the car parking areas (see Section 6) utilise a fitting which emits 0% upward light and provides for a safe and secure car park to give light levels adequate for sufficient CCTV coverage, where applicable. The luminaire utilised, offers a varied selection of optics specifically selected for the intended use which provides minimal backlight, reducing overspill at the boundary. The luminaire tilt will be in line with the guidance note GN01:2020 & the main beam angle will be less than 70° to keep nuisance glare down to a minimum.

BS5489-1:2020 provides guidelines for lighting performance criteria and the following assumptions are made:

New street Lighting to the existing access road will not be required as there is already existing public street lighting lanterns installed. Lighting to the existing running track and 3No MUGA pitches is to be retained with no additional works required as part of this application submission.

The spill light from the leisure will not affect the current road network. It is not envisaged the proposed scheme will not have any major impact on lighting levels surrounding the south of the site due to screening by existing hedgerow vegetation.



4.4 Summary Impact Table for Lighting Issues

Potential impact	Nature of impact Permanent or temporary	Significance Major, moderate, minor or neutral (positive or negative)	Mitigation / Enhancement measures	Residual effects Major, moderate, minor or neutral (positive or negative)
Lighting levels too bright	Permanent	Moderate	Design lighting to recommended guidelines and no greater, all light levels are as detailed within BS and Secured By Design Existing Lighting	Neutral
Light pollution spill from the site	Permanent	Majorly Negative	Utilise Fittings with excellent light control giving minimal spillage outside the boundary within figures laid down in CIBSE guidelines for spill & skyglow and ILE guidelines. Columns located around the edge of the lit area directed inwards. Minimum number of columns and heads used to achieve the specified light levels. Switch off when not in use and restrict hours of use.	Moderate Negative
Light glare from the site (including upward glow)	Permanent	Majorly negative	Utilise Fittings with excellent glare control giving minimum skyglow. Columns located around the edge of the lit area directed inwards. Minimum number of columns and heads used to achieve the specified light levels. Switch off when not in use and restrict hours of use.	Minor Negative
Unsightly columns and lighting heads	Permanent	Moderate negative	Within Car Parks the columns will be blended and finished to match in with the landscape scheme.	Minor Negative
Colour of light unacceptable	Permanent	Moderate	Use a lamp that generally is more acceptable to the public i.e. LED	Minor Negative



5.0 Control Measures

- 4.1 This section describes the particular control measures that this site will incorporate to minimise light spillage, trespass and pollution:
- 4.2 The external lighting shall be time controlled to ensure that the lighting installation only operates within the specified operating hours, and to provide a facility to switch part of the external lighting installation off during periods of low activity.
- 4.3 In addition, the external lighting installation shall incorporate a photo-electric cell control, to prevent the lighting installation operating during the hours of daylight, thus conserving energy and minimizing carbon emissions. The photo-electric cell set-point threshold shall be set at 50 lux.
- 4.4 A manual override control facility will be provided for testing and maintenance purposes only.
- 4.5 The whole of the external lighting installation will comply with the performance requirements set out within the ILE guidance note for reduction of light pollution.
- 4.6 The external lighting design will not incorporate any luminaires that have aiming angles beyond the horizontal working plane.
- 4.7 Measures shall be taken to eliminate light spillage onto adjacent land from luminaires positioned on the development site.
- 4.8 Illuminance levels will be reduced to the absolute legal minimum to conserve energy and to minimise light pollution.
- 4.9 The design shall incorporate measures to prevent light spillage onto adjacent land.
- 4.10 Where practically possible, all luminaires facing out of the development will be positioned to minimize direct visual contact with the lamp source.
- 4.11 The Preliminary Ecological Assessment (R2298b) section 1.1.7 advised that stie specific consideration shall be employed to particularly avoid lighting the tree lined margins, this has been adhered to be the selection and careful positioning of the luminaires.



6.0 Luminaire Selection

See Appendix B - Holophane Lighting Technical Submittal



7.0 Glossary

7.1 Symmetric & Asymmetric Distribution

The Image below illustrates the difference between an Asymmetric and a Symmetric distribution floodlight, with the symmetrical version the light is distributed evenly about a plane, with the asymmetrical version the light is distributed primarily in one direction.



If these fittings are mounted at too extreme an angle, then the result will be excessive amounts of light directed above the horizontal plane (i.e. upwards light) – this is an obvious case of “skyglow”



Effect of mounting at extreme angles

As can be seen in the illustrations above, the effect is considerably worse with the asymmetric version. Taking this into account we have decided on this project not to mount floods on the building to avoid this issue, instead they shall be column mounted.

7.2 Glossary of Terms

Skyglow - Defined as the brightening of the night sky around the development.

Lux - A standard unit of light measurement.

Nuisance glare - The perceived brightness of an object viewed against a dark background – may cause annoyance.

Light trespass / Spill - Spill of light beyond the site boundary.

Uniformity (Emin/Eave) - Minimum to average lighting level.

Maintained Illuminance - The specified light level (lux) after 2/3000 hours of operation

Skyglow - The brightening of the night sky around the development

Upward Light Ratio (ULR) - Amount of light emitted upwards from the light fitting Defined as a percentage of amount of downward light ie 95% ULR (5 % lost upwards to sky)



8.0 Design Measures for Biodiversity

Refer to the preliminary ecology report prepared by John Wenman the Ecology Consultants and the relevant extracts relating to the operational mitigation of the spill of the external lighting and the potential impact to the surrounding habitat.



9.0 Conclusion.

Lighting in itself is not a problem; it only becomes a problem where it is excessive, poorly designed or badly installed (Lighting in the Countryside, Towards Good Practice: 2006).

Additional Design & control measures for providing artificial external lighting have been considered and have been incorporated into the external lighting design, where required to comply with Reading Borough Council Planning discharge conditions.

- 9.1 The designed lighting solution has been carefully generated to ensure the immediate environment has been protected including the surrounding areas that border the development and to reduce light spill to areas beyond this.
- 9.2 Careful consideration has been appropriated to ensure that the safe operation and movement of vehicular traffic and pedestrians, emphasising reduction of glare through choice of luminaires and efficient mounting heights.
- 9.3 It should also be noted that the illumination has been designed to meet operational and security requirements, whilst ensuring the design takes into consideration and limits light pollution and unobtrusive light impacting on the surrounding amenity and ecological zones (see 4.2 above).
- 9.4 The lighting has been kept to a practical standard using a mixture of efficient high-quality building and column mounted luminaires which have been chosen to minimise impact on the natural environment including further consideration on ecological constraints. Full descriptions and details of the proposed luminaires are as detailed in appendix B of this report.
- 9.5 Overall the proposed development requires appropriate levels of illumination throughout to satisfy the intended use of the site.
- 9.6 With prime focus and our careful consideration of the site and the proposed development, this has determined an outcome of providing an external lighting strategy that will create an acceptable lighting environment that accords with the needs of the occupier and the local policies, guidance and industry standard

It is concluded that the external lighting design, factoring in all the above considerations with careful luminaire selection and luminaire positioning will not individually or cumulatively have an adverse impact on the surrounding environment.



Appendix A – Proposed External Lighting Layout

See TLP Drawing Reference: C7402-TLP-00-00-DR-E-801

Appendix B – Proposed Light Fitting Technical Submittal

See Holophane Data Sheets Enclosed

Scale 1:500 [m]

CIBSE LIGHTING GUIDE LG6 – (2016) THE EXTERIOR ENVIRONMENT

C7402 - TLP - 00 - 00 - DR - E - 801 A

> DATASHEET

ROADWAY - FTS

FTS.3.LA103.FW.C9

SALES CONTACT: Dan Jakeman

PROJECT: P173-1313 - Palmer Park Leisure Centre

ITEM REF: A1



Product image may not represent the final configuration stated above.




PRODUCT SPECIFICATION

 [FTS HOLOPHANE WEBSITE](#)

FTS.3.LA103.FW.C9

Holophane Factor Small luminaire with an IP66 LED light engine module comprising and die-cast aluminium finned body that conforms to EN1706 AC-46500. Tool-less access via trigger latch hinging door to the driver and electrical termination compartment. This specific SKU includes:

- Series 3
- LED light engine producing c.10,000 lm with a nominal 3000°K colour temperature
- Forward throw light distribution
- Metallic Silver (RAL9006)



FTSB.6.1S.SA42.LMZ.GV9

Holophane tubular base compartment column for use with Factor Small Luminaires. 6 metre, Single head short bracket (300mm outreach), Side arm bracket suitable for 42mm entry. For light & medium area wind zones (compliant to EN40).

- Bracket galvanised and painted metallic silver (RAL9006)
- Direct embedment

PERFORMANCE DATA

Drive Current: 1225mA

Lumens: 8,978

CCT: 3000K

CRI: 70

Inrush: 43A - 0.26ms

Power: 78W

Fitting Current: 0.35A



7 Kg




0.071 M₂



[Download Installation Guide](#)


DIMENSIONS




PHOTOMETRY



Polar Plot




Isoilluminance Plot




IES File: FTS.3.LA103.FW

LLMF GRAPH



For reference purposes, the graph extrapolates beyond the recommend 6x LM-80 data in TM-21, which our calculations are based on. Graph shows data for LxxB50.

COLOUR TEMPERATURES



COLOURS

Selected Colour


	C9	Metallic Silver (RAL9006)
--	-----------	---------------------------

Custom Colour

	RAL***	Customer specified colour
--	---------------	---------------------------

*Choosing a custom colour may increase the cost and lead time.

Available Colours

	C1	Smooth White (RAL9016)
	C4	Smooth Graphite (RAL7011)
	C6	Smooth Grey (RAL7035)
	C7	Textured Black (RAL9005)
	C9	Metallic Silver (RAL9006)

Lumen data is considered to be representative of the configuration shown, and may vary, with a tolerance on flux of +/- 7% (typical of LED manufacturer's data) and luminaire power of +/- 5%.

The specifications of the Holophane luminaires represents typical values. All descriptions, illustrations, drawings and specifications in the Holophane catalogue, data sheets and website represent only general particulars of the goods to which they apply and shall not form part of any contract. The company reserves the right to change specifications at its discretion without prior notification or public announcement.



Product image may not represent the final configuration stated above.



PRODUCT SPECIFICATION




FTS HOLOPHANE WEBSITE

FTS.3.LA103.SY.C9

Holophane Factor Small luminaire with an IP66 LED light engine module comprising and die-cast aluminium finned body that conforms to EN1706 AC-46500. Tool-less access via trigger latch hinging door to the driver and electrical termination compartment. This specific SKU includes:

- Series 3
- LED light engine producing c.10,000 lm with a nominal 3000°K colour temperature
- Symmetrical light distribution
- Metallic Silver (RAL9006)



FTSB.6.1S.SA42.LMZ.GV9

Holophane tubular base compartment column for use with Factor Small Luminaires. 6 metre, Single head short bracket (300mm outreach), Side arm bracket suitable for 42mm entry. For light & medium area wind zones (compliant to EN40).

- Bracket galvanised and painted metallic silver (RAL9006)
- Direct embedment

PERFORMANCE DATA

Drive Current: 1225mA

Lumens: 9,190

CCT: 3000K

CRI: 70

Inrush: 43A - 0.26ms

Power: 78W

Fitting Current: 0.35A



7 Kg




0.071 M₂



[Download Installation Guide](#)


DIMENSIONS




PHOTOMETRY



Polar Plot




Isoilluminance Plot




IES File: FTS.3.LA103.SY

LLMF GRAPH



For reference purposes, the graph extrapolates beyond the recommend 6x LM-80 data in TM-21, which our calculations are based on. Graph shows data for LxxB50.

COLOUR TEMPERATURES



COLOURS

Selected Colour


	C9	Metallic Silver (RAL9006)
--	-----------	---------------------------

Custom Colour

	RAL***	Customer specified colour
--	---------------	---------------------------

*Choosing a custom colour may increase the cost and lead time.

Available Colours

	C1	Smooth White (RAL9016)
	C4	Smooth Graphite (RAL7011)
	C6	Smooth Grey (RAL7035)
	C7	Textured Black (RAL9005)
	C9	Metallic Silver (RAL9006)

Lumen data is considered to be representative of the configuration shown, and may vary, with a tolerance on flux of +/- 7% (typical of LED manufacturer's data) and luminaire power of +/- 5%.

The specifications of the Holophane luminaires represents typical values. All descriptions, illustrations, drawings and specifications in the Holophane catalogue, data sheets and website represent only general particulars of the goods to which they apply and shall not form part of any contract. The company reserves the right to change specifications at its discretion without prior notification or public announcement.

> DATASHEET

EXTERNAL - DEB

DEB.L014.PAY.DO.H100.C9.MCB

SALES CONTACT: Dan Jakeman

PROJECT: P173-1313 - Palmer Park Leisure Centre

ITEM REF: B



Product image may not represent the final configuration stated above.




PRODUCT SPECIFICATION

[WWW.DEB.HOLOPHANE.WEBSITE](#)

Holophane Denver Elite bollard luminaire. Tri-lobular extruded marine grade aluminium body with die-cast aluminium top and base secured by stainless steel nuts and sealed to IP65. The optical arrangement with PrismaLED lenses and unique patented decorative gasket highlight feature. Suitable for flange base mounting (bolts available as an accessory).

This specific SKU includes:

- LED light engine producing c.1,000 lm with a nominal 4000K colour temperature
- Asymmetric distribution
- Double sided
- 1 metre high
- Metallic Silver (RAL9006)
- Mini circuit breaker



PERFORMANCE DATA

Drive Current:	350mA
Lumens:	815
CCT:	4000K
CRI:	70
Inrush:	20A - 0.05ms
Power:	12W
Fitting Current:	0.05A




19.5 Kg



[Download Installation Guide](#)


DIMENSIONS




PHOTOMETRY

[↓ IES FILE](#)

Polar Plot




Isoilluminaance Plot



IES File: DEB.L014.PAY.DO

LLMF GRAPH



For reference purposes, the graph extrapolates beyond the recommend 6x LM-80 data in TM-21, which our calculations are based on. Graph shows data for LxxB50.

► 4000K

COLOURS

Selected Colour

C9 Metallic Silver (RAL9006)

Custom Colour

RAL**** Customer specified colour

*Choosing a custom colour may increase the cost and lead time.

Available Colours

C1 Smooth White (RAL9016)

C4 Smooth Graphite (RAL7011)

C6 Smooth Grey (RAL7035)

C7 Textured Black (RAL9005)

C9 Metallic Silver (RAL9006)

Lumen data is considered to be representative of the configuration shown, and may vary, with a tolerance on flux of +/- 7% (typical of LED manufacturer's data) and luminaire power of +/- 5%.

The specifications of the Holophane luminaires represents typical values. All descriptions, illustrations, drawings and specifications in the Holophane catalogue, data sheets and website represent only general particulars of the goods to which they apply and shall not form part of any contract. The company reserves the right to change specifications at its discretion without prior notification or public announcement.

> DATASHEET

EXTERNAL - DEW

DEW.LAO13.CGL.NR.C9

SALES CONTACT: Dan Jakeman
PROJECT: P173-1313 - Palmer Park Leisure Centre
ITEM REF: C



Product image may not represent the final configuration stated above.




PRODUCT SPECIFICATION

www.dew-holophane.com **DEW HOLOPHANE WEBSITE**

Holophane Denver Elite Wall luminaire. Tri-lobular wall mounted luminaire manufactured from LM6 marine grade die-cast aluminium body, with integrated thermal management design. Optical arrangement with aluminium internal reflector and PrismaLED prismatic soda lime or clear glass lens dependent on optical distribution. Sealed to IP65 and suitable for wall mounting with rear, top, side and through wiring options via 20mm Ø knockout cable entry/exit points.

This specific SKU includes:

- LED light engine producing c.1,000 lm with a nominal 3000°K colour temperature
- Clear glass lens
- Long and Narrow light distribution
- Metallic Silver (RAL9006)



PERFORMANCE DATA

Drive Current: 350mA

Lumens: 1,142

CCT: 3000K

CRI: 70

Inrush: 15A - 0.36ms

Power: 12W

Fitting Current: 0.05A




6.4 Kg



[Download Installation Guide](#)


DIMENSIONS




PHOTOMETRY

[↓ IES FILE](#)

Polar Plot




Isoillumination Plot




IES File: DEW.LA013.NR.CGL

LLMF GRAPH



For reference purposes, the graph extrapolates beyond the recommend 6x LM-80 data in TM-21, which our calculations are based on. Graph shows data for LxxB50.

COLOUR TEMPERATURES



COLOURS

Selected Colour

C9	Metallic Silver (RAL9006)
-----------	---------------------------

Custom Colour

RAL****	Customer specified colour
----------------	---------------------------

*Choosing a custom colour may increase the cost and lead time.


Available Colours

C1	Smooth White (RAL9016)
C4	Smooth Graphite (RAL7011)
C6	Smooth Grey (RAL7035)
C7	Textured Black (RAL9005)
C9	Metallic Silver (RAL9006)

Lumen data is considered to be representative of the configuration shown, and may vary, with a tolerance on flux of +/- 7% (typical of LED manufacturer's data) and luminaire power of +/- 5%.


The specifications of the Holophane luminaires represents typical values. All descriptions, illustrations, drawings and specifications in the Holophane catalogue, data sheets and website represent only general particulars of the goods to which they apply and shall not form part of any contract. The company reserves the right to change specifications at its discretion without prior notification or public announcement.

standard columns stepped steel



Holophane products that are suitable

CityMax
Denver Elite pole
D-Series
Factor
Factor small
V-Max



	Nominal Height	Base Diameter*	Base Height	Planting Depth	Overall Length	Door to Ground	Door Opening Length	Door Opening Width	Spigot Length*	Spigot Diameter*	Shaft Diameter*	Weight kg*	Bending Moment (ULS) Nm
description	A	B	C	D	E	F	G	H	I	J	K		
2.5m standard duty	2500	140	1075	800	3300	400	500	100	-	-	76	27	2100
3m standard duty	3000	140	1075	800	3800	400	500	100	-	-	76	30	4666
3.5m standard duty	3500	140	1075	800	4300	400	500	100	-	-	76	32	2100
4m standard duty	4000	140	1075	800	4800	400	500	100	-	-	76	34	6484
4.5m standard duty	4500	140	1075	800	5300	400	500	100	-	-	76	37	5108
5m standard duty	5000	140	1075	800	5800	400	500	100	-	-	76	39	6149
5.5m standard duty	5500	140	1075	1000	6500	400	500	100	-	-	76	44	6003
6m standard duty	6000	140	1075	1000	7000	400	500	100	-	-	76	46	5999
6m heavy duty	5700	168	1200	1000	6700	400	600	115	130	76	89	71	10404
8m standard duty	7700	168	1200	1200	8900	400	600	115	130	76	89	89	10072
8m heavy duty	7700	168	1300	1200	9000	500	600	115	250	101	114	107	15699
8m extra heavy duty	7700	194	1300	1200	9000	500	600	115	250	127	140	136	18973
10m standard duty	9700	168	1300	1500	11200	500	600	115	250	101	114	150	18067
10m heavy duty	9700	194	1300	1500	11200	500	600	115	250	127	140	168	23193
10m extra heavy duty	9700	194	1300	1500	11200	500	600	115	250	152	168	220	28317
12m standard duty	11700	194	1300	1700	13400	500	600	115	250	127	140	213	26251
12m heavy duty	11700	194	1300	1700	13400	500	600	115	250	127	168	260	40390

* Exclusion TBC

2.5m standard duty Flange Plate FB2 Bolt M18 x 120

Flange Plate and Anchor Bolt information will be confirmed at time of order due to the necessity in ensuring



standard columns stepped steel - CityMax Large only

post top

	Nominal Height	Base Diameter	Base Height	Planting Depth	Overall Length	Door to Ground	Door Opening Length	Door Opening Width	Spigot Length	Spigot Diameter	Shaft Diameter	Weight kg	Bending Moment (ULS) Nm
description	A	B	C	D	E	F	G	H	I	J	K		
6m	6000	140	1075	1000	7000	400	500	115	-	-	-	46	5999
8m	7700	168	1300	1200	9000	500	600	115	100	76	114	107	15699
10m	9700	168	1300	1500	11200	500	600	115	100	76	114	150	18067
12m	11700	194	1300	1700	13400	500	600	115	100	76	140	168	26251
15m	14700	194	1200	2000	17000	400	600	115	100	76	168	306	40300

twin head

	Nominal Height	Base Diameter	Base Height	Planting Depth	Overall Length	Door to Ground	Door Opening Length	Door Opening Width	Spigot Length	Spigot Diameter	Shaft Diameter	Weight kg	Bending Moment (ULS) Nm
description	A	B	C	D	E	F	G	H	I	J	K		
8m	7400	194	1200	1200	8800	400	600	115	200	127	139.7	125	22610
10m	9400	194	1200	1500	11100	400	600	115	200	152.4	168.3	208	39131
12m	11400	194	2500	1700	13300	1000	600	115	200	152.4	168.3	295	41585

Note: For Terrain Category 2 locations LMZ, HVZ & HEZ


Anchor bolts

For columns supplied with optional flange base Holophane offer three types of foundation bolts.

Note: The material used for the bolts is Fe E500 grade steel, with yield strength 500 N/mm² and minimum UTS 550 N/mm².

HEL.FS1 M18 Bolts (FS1) x 400 mm long

HEL.FS2 M24 Bolts (FS2) x 820 mm long



SUMMARY

P173-1313 - PALMER PARK LEISURE CENTRE

Line No.	Item Ref	Quantity	Catalogue
LUMINAIRE, COLUMN AND BRACKET PACKAGE			
10	A1	8	FTS.3.LA103.FW.C9
11	A1	8	FTSB.6.1S.SA42.LMZ.GV9
LUMINAIRE, COLUMN AND BRACKET PACKAGE			
30	A2	4	FTS.3.LA103.SY.C9
31	A2	4	FTSB.6.1S.SA42.LMZ.GV9
LUMINAIRE			
60	B	11	DEB.L014.PAY.DO.H100.C9.MCB
ACCESSORY			
70		11	DEB.ROOT
LUMINAIRE			
80	C	9	DEW.LA013.CGL.NR.C9