

MELODIE

CLAY INTERLOCKING PANTILES



Melodie is a single interlocking clay pantile with a flexible gauge and a robust interlock, enabling it to perform at pitches as low as 12.5°. Available in a Natural Red colour.

A clay left hand verge tile provides a neat finish at the roof edge. Concrete segmental ridge and hip tiles can be used in conjunction with Universal RidgeFast and HipFast systems for ventilation purposes and to provide a completely dry fixed solution.

TECHNICAL TOOLKIT

Marley provides a comprehensive technical service and a range of online tools to ensure design performance and compliance to the latest British Standards and NHBC technical guidelines. These services include:

- ▲ Fixing specifications: marley.co.uk/tilefix
- ▲ NBS clauses: marley.co.uk/specrite
- ▲ CAD details: marley.co.uk/cad
- ▲ BIM models: marley.co.uk/bim

For more information on the recent update to the British Standard for Slating and Tiling (BS 5534) and how it might affect your project, please visit marley.co.uk/BS5534

COLOUR AVAILABILITY

See pages 22-23 for more detailed colour panels.



TECHNICAL DATA

Size of tile	440mm x 255mm	
Minimum pitch*	12.5°	
Maximum pitch	70°	
Minimum headlap	92mm	
Batten spacing	Minimum 314mm	Maximum 348mm
Cover width	209mm (nominal)	
Covering capacity (net)	13.8 tiles/m² at 92mm gauge	
Weight of tiling	44kg/m² at 92mm headlap (approx.)	
Battens required	2.88 lin.m/m² at 92mm headlap	
Batten size recommended	38 x 25mm for rafters/supports not exceeding 450mm centres (fixed to BS 5534)	
	50 x 25mm for rafters/supports not exceeding 600mm centres (fixed to BS 5534)	
Tile nails	45mm x 3.35mm aluminium clout head	
Fixing clips	Eaves, verge and tile clips	

* The minimum recommended pitch and lap may be influenced by special circumstances, please contact the Technical Advisory Service.