




A versatile hinged system with slim sections and flush hinges suitable for treating windows and standard sized doors. Single casements with a secure lock option achieve Secured by Design accreditation.



FEATURES

- Available in single side hung, top hung, bottom hung, double casement and stable door designs
- Double casement and stable door provide full access
- Strong, purpose designed flush hinges colour matched to frame
- Colour matched non-locking handle (ref H7)
- Multipoint locking (ref L20)
- 90° restrictor stay to side hung
- Ratchet stay to top hung (ref L26)
- Twin compression seals ensure high sealing efficiency
- Fixings concealed within the frame - trims not required
- Frames may be linked with a colour matched aluminium transom/mullion section

DIMENSIONS

Recommended maximum frame

Format	Height (mm)	Width (mm)
SINGLE SIDE HUNG	2200	1300
TOP/BOTTOM HUNG	1300	1300
DOUBLE CASEMENT	2200	2600
STABLE DOOR	2200	1100

Minimum side hung sash (h)700mm x (w)450mm

Minimum top/bottom hung sash (h)400mm x (w)500mm



FRAME COLOUR

Stock finish is white HIPCA 9910 semi-gloss

Any standard powder paint, wood grain finish or anodised finish to order

OPTIONS

Glazing	4mm to 6.8mm
Frames	Curved head or jamb – minimum radius 450mm 'No threshold' cill (ref F12)
Ironmongery (see page 44/45)	H6 Locking slimline handle H8 Locking handle H9 Rosette -square drive with removable key H12, H15, H16 Feature handles H18 Vivo low-profile handle H21 Flush lock with cover disc H22 Flush lock with security cover plate L7 Spring catch L15 Multipoint locking (SBD/EXV33) L29 Sprung restrictor stay