

The Oracle Shopping Centre, Bridge Street, Reading, RG1 2AG

Approved Signage (Ref. 170800)

Type of Sign (Fascia or Totem)	Ref and Location	Height from the Ground to the Base	Height	Width	Depth	Materials	Maximum Height of Individual Letters and Symbols	Colour of Text and Background	Illumination	Internal or External Illumination?	Illuminance levels Total	Static or Intermittent Illumination
Fascia	EXT 06 Riverside Car Park entrance	2560mm	900mm	10550mm	100mm – 200mm (TBC following development of lighting detail, which may dictate an increase to depth)	Fabricated aluminium sign panel of appropriate thickness with internal support as required to ensure no warping or flexing across face. Sign box to have crisp 90 degree corners. Opal acrylic graphics pushed through aluminium face to finish flush. Graphics to have crisp edges and sharp corners.	450mm	Panel painted black to all sides and edges. Letters to illuminate white. 'P' icon to illuminate white and blue.	Yes	Internal	346 cd/m2	Static
Fascia	EXT 08 Riverside Car Park entrance	2560mm	805mm	3892mm	100mm – 200mm (TBC following development of lighting detail, which may dictate an increase to depth)	Fabricated bronze background and anodised aluminium face panel with graphic letters cut through. Illumination between background and anodised aluminium panel. Combined with fabricated aluminium sign panel of appropriate thickness with internal support as required to ensure no warping or flexing across face. Sign box to have crisp 90 degree corners. Opal acrylic graphics pushed through aluminium face to finish flush. Graphics to have crisp edges and sharp corners.	260mm	Letters are cut into anodised aluminium face panel to show bronze background behind the cut out text. Combined with panel painted black to all sides and edges. Letters to illuminate white. 'P' icon to illuminate white and blue.	Yes	Internal	334 cd/m2	Static
Fascia	EXT 31 Holy Brook Car Park entrance	2560mm	1125mm	8471mm	100mm – 200mm (TBC following development of lighting detail, which may dictate an increase to depth)	Fabricated bronze background and anodised aluminium face panel with graphic letters cut through. Illumination between background and anodised aluminium panel. Combined with fabricated aluminium sign panel of appropriate thickness with internal support as required to ensure no warping or flexing across face. Sign box to have crisp 90 degree corners. Opal acrylic graphics pushed through aluminium face to finish flush. Graphics to have crisp edges and sharp corners.	360mm	Letters are cut into anodised aluminium face panel to show bronze background behind the cut out text. Combined with panel painted black to all sides and edges. Letters to illuminate white. 'P' icon to illuminate white and blue.	Yes	Internal	279 cd / m2	Static