



MODULO 2 LED

LED XL.W2C1 consiste en un nodo con cubierta en plástico de gran durabilidad y que incorpora 2 LEDS en un formato con una potencia de 0.48W por placa; optimizando la salida luminica al emitirse desde un único punto.
Las placas disponen de un cable de interconexión que permite crear una cadena.

Para un rendimiento óptimo de luminosidad de los leds se debe utilizar máximo 80% y mínimo 60 % de la potencia fuente de alimentación.

EJEMPLO:

Para una fuente de alimentación de 150W se colocaran entre 130 a 250 piezas.



IP68

GARANTÍA 5 AÑOS

ESPECIFICACIONES MODULO 2 LEDS

Modelo	Color	Gama Voltaje	P (W)	Luminancia	Inspección de ángulo	Dimensiones L X W X H
XL. R2C1	R	12± 10%	0.48	2.350	120	63.0 X 15.0 X 9.0
XL. G2C1	G			3.600		
XL. B2C1	B			1.160		
XL. W2C1	W			8.000		



SMC CHANNEL Letter Module (2 LEDs White Color)

Model Name		XL.W2B1		COLOR		2 LEDs White	
PARAMETER		MIn	Tpy	Max	Unit	etc	
	Input Voltage	11.4	12.0	12.6	V		
	Opetating Curret		40		mA		
	Power Consumption		0.48		W		
	Brightness	8.600	9.200	10.000	med		
	Drinving Method	Polarity Static Current					
	Viewing Angle	120			deg		
	Kelvin Temperature	10.000	-	14.000	K		
	Dimension	61.0 x 16.0 x 10.0			mm		
	Weight of Unit				g		
	Span of Unit		150				
	Protection Rating	IP 68					
	Radiation Pattern		120		deg		
	Raten Lifetime		50.000			Normal Temperature: 25 C	
	Operating Temperature	- 20		50	C		
	Storage Temperature	- 30		80	C		
	Module Q'ty Per SMPS	60 W		96 Und.	EA	SMPS OUT V 12 V	
		100 W		160 Und.			
		150 W		250 Und.			
		200 W		330 Und.			
	Lead Wire	UL1015#18					