

PRODUCT DATA SHEET

Haired Coarse Stuff

Description	A chalk lime putty based mortar/plaster with a blend of sands and grit with the addition of animal hair (1kg/tonne).
1. Colour code	BL40H Chalk white:
Aggregate blend	Wareham washed sharp sand, Newbury Grit sand, Wareham sieved playpit sand.
2. Colour code	LS2H Oatmeal:
Aggregate blend	Frith End Blend, Wareham washed sharp sand, Newbury Grit sand.
Lime Putty	Singleton Birch chalk lime putty matured min 1 month
Aggregate size	<4mm
Mix ratio	1:3 lime/sand
Uses	As an internal or external base coat.
Approximate Coverage	1m ² /25kg at 10mm thickness onto wooden lath. 1.2m ² /25kg at 10mm thickness onto solid substrate.
Shelf Life	Avoid exposure to excess heat or cold. Lime plaster matures and improves with age when kept sealed. However, the hair will deteriorate if kept for prolonged periods. Use within 2 weeks of manufacture or add more hair if kept for longer.
Units	25kg plastic tub, 25kg plastic bag, 500kg bulk bag, 1000kg bulk bags.
Health and Safety	Contains Calcuim Hydroxide CA(OH)². R36/38 Irritating to skin and eyes. R41 Risk of serious damage to eyes. R66 Repeated exposure may cause skin dryness and cracking. S36/37/39 Wear suitable protective clothing, gloves and eye/face protection. S26 In case of contact with eyes, rinse immediately with plenty of clean water and seek medical attention. S28 After contact with skin, wash immediately with plenty of water. S2 Keep out of the reach of children.
Observations	Recommended to be used by professional tradesmen experienced in the application of lime plasters.
Technical Advice	Call 01794 884294 or email info@limestuff.co.uk