

[Home \(/\)](#)

Alitherm Heritage 60

Single and double doors with enhanced thermal performance that are ideal for refurbishment projects

PRODUCT SHOWCASE



Product information

Description

Specification

Performance

Dimensions

Downloads

Fully compliant with Document L of the Building Regulations, the Smart Alitherm Heritage 60 range of single and double doors provides an elegant solution for both new build and refurbishment projects.

The doors' distinctive slim sightlines perfectly complement Smart's existing Alitherm Heritage window range, which together mimic the appearance of traditional steel windows and doors – while delivering all the performance benefits of a modern aluminium system.



Threshold view



Providing a ready replacement for steel doors on heritage applications, such as building renovations or apartment conversions. Alitherm Heritage 60 doors are suitable for sensitive conservation areas, where planning regulations require a like-for-like product replacement.

Featuring an enhanced thermal break offering U Values from 1.4 W/m²K (double glazed) and 1.1 W/m²K (triple glazed). Fully compliant with Document L.

Range of single and double doors, each with open-in and open-out options. Elegant slim sightlines create a clean and elegant aesthetic.

High quality, high performance solutions for a broad range of applications.

Complementary range of hardware and extensive palette of colour options

Door Type	Max W (mm)	Max H (mm)	Frame Depth (mm)	Opening	Air
Single	900	2100	67.5	In	4, 600Pa
Single	900	2100	67.5	Out	4, 600Pa
Double	900	2100	67.5	In	4, 600Pa
Double	900	2100	67.5	Out	4, 600Pa



Width/height per sash. Dimensions for doors with approved sash profiles.



Frame head view



Double door meeting style view

Glazing Type	DSER	Typical U Value	C
--------------	------	-----------------	---

Triple	A Rating with 0.7 W/m2K	1.1 W/m2K with 0.7 W/m2K centre pane	
--------	----------------------------	---	--

Double	C Rating with 1.0 W/m2K	1.4 W/m2K with 0.9 W/m2K centre pane 1.5 W/m2K with 1.0 W/m2K centre pane	
--------	----------------------------	--	--

