




1. Schedule of Luminaires

Notes:

1. All lamps shall be colour temperature 4000K with a colour rendering of group 1B (>RA80) unless stated otherwise.
2. Any luminaire reference may be suffixed with the letter 'E'. This denotes an integral maintained 3 hour emergency version of the luminaire as described.
3. The description of any luminaire shall be deemed to include any additional fixing items required to suit the mounting of the luminaire.
4. All LED luminaires without integral drivers shall be provided with appropriate remote drivers supplied by the luminaire manufacturer.

Reference	Manufacturer	Range	Description	Lamp	Efficacy	Image
A	Whitecroft	Tegan 2 Surface	600x600mm surface mounted luminaire c/w steel body finished in white, surface mounting kit, opal TP(b) diffuser, integral DALI 2 dimmable driver and 3-hour emergency pack.	41W LED 5128lm	125lm/W	
B	Whitecroft	Kolo Surface	IP44, 400mmØ surface mounted bulkhead luminaire c/w cast aluminium body finished in white, polycarbonate opal TP(a) diffuser, trim ring, integral driver and 3-hour emergency pack.	28W LED 3549 lm	128 lm/W	



Reference	Manufacturer	Range	Description	Lamp	Efficacy	Image
C	Whitecroft	ACL Industry	IP66/IK08, Surface mounted linear luminaire c/w GRP body finished in grey, opal polycarbonate diffuser, stainless steel clips, integral driver and 3-hour emergency pack.	25W LED 3970lm 4000K	156lm/W	
D	Thorn Lighting	Piazza II LED	IP65, IK10 Surface wall mounted luminaire c/w die cast aluminium back plate, polycarbonate body finished in anthracite, textured clear polycarbonate diffuser integral driver and 3-hour emergency pack.	15W 1844lm 4000K	116lm/W	



Reference	Manufacturer	Range	Description	Lamp	Efficacy	Image
EX1	IGuzzini	Light Up ES53	IP66, IK09 floor-recessed uplight c/w flush mounted all glass cover, 30° beam flood optic, Installation mounting kit, black serigraphy, stainless steel cable gland, mounting brackets (anchors), remote driver.	4W LED 403lm 4000K	140lm/W	
EXIT	Whitecroft	Egress Exit	Surface mounted, maintained illuminated exit sign c/w polycarbonate body finished in white, ISO legend (direction to suit location), integral driver and 3-hour emergency pack.	3.2 Watt	n/a	