

SAFETY DATA SHEET

According to UK REACH (Annex II) and UK CLP

1. Identification of the substance/mixture and of the company

Product name: Tuff Grip Clear (W/B)

Product type: High-performance, water-based acrylic textured coating

Relevant identified uses:

High-performance, water-based acrylic textured coating for slip resistance

Uses advised against:

Any use other than as intended

Supplier:

SlipDoctors

2101 Midway Road, Suite #350

Carrollton, TX 75006, United States

Emergency telephone number:

Not available. No dedicated UK emergency number provided.

2. Hazards identification

Classification (UK CLP):

Reproductive toxicity, Category 1B – H360

Skin irritation, Category 2 – H315

Eye irritation, Category 2 – H319

STOT (single exposure), Category 3 – H335

Aquatic Chronic, Category 1 – H410

Signal word: Danger

3. Composition/information on ingredients

Mixture

2-Butoxyethanol (CAS 111-76-2): 1–5%

Butyl benzyl phthalate (CAS 85-68-7): 1–5%

Exact percentages are withheld as trade secrets in accordance with UK REACH.

4. First aid measures

If exposed or concerned, seek medical advice. Rinse eyes with water for several minutes if exposed. Wash skin with soap and water. Remove to fresh air if inhaled. Do not induce vomiting if swallowed.

5. Firefighting measures

Use water spray, foam, dry chemical or carbon dioxide. Thermal decomposition may produce carbon monoxide and carbon dioxide. Firefighters should wear self-contained breathing apparatus.

6. Accidental release measures

Avoid breathing vapours or mists. Prevent entry into drains or waterways. Absorb spills with inert material and dispose of according to regulations.

7. Handling and storage

Avoid contact with skin and eyes. Store locked up in a cool, well-ventilated place. Protect from freezing.

8. Exposure controls/personal protection

UK WEL for 2-Butoxyethanol: 20 ppm (8h TWA). Use adequate ventilation. Wear protective gloves, goggles and suitable respiratory protection if required.

9. Physical and chemical properties

Liquid; milky appearance; slight odour. Flash point >93°C. Soluble in water. Relative density 1.041. VOC approx. 34.5 g/L.

10. Stability and reactivity

Stable under normal conditions. No hazardous reactions expected. Decomposition may produce carbon oxides.

11. Toxicological information

May cause skin and eye irritation. May cause respiratory irritation. May damage fertility or the unborn child.

12. Ecological information

Very toxic to aquatic life with long lasting effects. Avoid release to the environment.

13. Disposal considerations

Dispose of contents and container through a licensed waste contractor in accordance with UK regulations.

14. Transport information

Not regulated for transport under ADR/RID, IMDG or IATA.

15. Regulatory information

UK REACH: Imported at less than 1 tonne per year per substance; registration not required under Article 6.
UK CLP: Classified and labelled in accordance with UK CLP.

16. Other information

Revision status: UK REACH Annex II SDS
Revision date: 05 February 2026

This SDS is intended to describe health, safety and environmental requirements under UK REACH.